BLACK WALNUT steamed - CHERRY natural|steamed - ELM steamed MAPLE - OAK - PEAR steamed - SMOKED OAK - SMOKED ZIRNOAK



Woodtype	ASH
----------	-----

Description 3 layers of the same hardwood. The Ash without heartwood has a light yellow

to slightly brownish colour. The sorting Auslese is essentially knot-free\*, with a simple

structure.

Brinell hardness 4,5 kp Gross density 0,69 g | cm³

## 1-Strip Country House Flooring ASH Auslese "St.Pölten"



## Surfaces

- Oil | wax oxidative dried
- ✓ Varnished 7-times
- ✓ Untreated sanded
- **✓** Brushed
- **▼** Bevel
- ✓ Special colour



Sorting guidelines	
Healthy knots	to approx. 5 mm allowed
Black knots	to approx. 5 mm allowed
Healthy red heart	not allowed
Healthy black heart	not allowed
Cracks	not allowed
Curled Spots   differences in structure	slightly allowed
Natural colour differences	slightly allowed
Natural fiber orientation	slightly allowed
Wormholes and insect-ate-spots	not allowed
Sapwood	not allowed
Red or brown spots	not allowed
Stains from storage and light blueness	not allowed
Knocked spots	not allowed
Mirror	not allowed

	Syn	nbol picture - may vary in colour and structure
Technical data		
Thickness 15 mm Width 150 mm	n	Useful layer approx. 5 mm
	system s   pkg)	6 layers 1900 mm 2 layers 950* mm
Connection Tongue and groove  One layer 950* mm consists of 2 boards		
m²   pkg. 2,28		m² pal. 111,72
kg pkg. 23		kg pal. 1127
✓ Floating laying		
✓ Glued laying		
m²   pkg. 2,28 kg   pkg. 23 ✓ Floating laying		m² pal. 111,72

✓ Suitable for underfloor heating

when gluing the entire area with solvent-free adhesives



Symbol picture - may vary in colour and structure