

Woodtype **OAK european**

Description 3 layers of hardwood. The European Oak has a middle brown to intensive brown colour. The sorting Design is slightly to very knotty, with a lively structure.

Brinell hardness 4,2 kp The creative program consists of 3 layers hardwood, where the  
 Gross density 0,71 g | cm³ middle layer and the under layer can vary to the top layer.

1-Strip Country House Flooring OAK european Design Kreativ „Villach“



Surfaces

- Oil | wax oxidative dried
- Varnished 7-times
- Untreated sanded
- Brushed
- Bevel
- Special colour



Symbol picture - may vary in colour and structure

Sorting guidelines	
Healthy knots	allowed (partly filled)
Black knots	allowed (partly filled)
Healthy red heart	not allowed
Healthy black heart	not allowed
Cracks	allowed (partly filled)
Curled Spots   differences in structure	allowed
Natural colour differences	allowed
Natural fiber orientation	allowed
Wormholes and insect-ate-spots	not allowed <small>are allowed in middle layer and back layer**</small>
Sapwood	partly allowed
Red or brown spots	allowed
Stains from storage and light blueness	allowed
Knocked spots	not allowed
Mirror	alongside and crosswise allowed

Technical data		
Thickness	10,7 mm	Useful layer approx. 3 mm
Width	150 mm	
Length	Lengthsystem	7 layers 1900 mm
	(11 layers   pkg)	4 layers 950* mm
Connection	Tongue and groove	<small>Due to the technical drying, there are no longer any pests, only the holes in the middle layer and back layer**</small>
<small>One layer 950* mm consists of 2 boards</small>		
m²   pkg. 3,14		m²   pal. 109,90
kg   pkg. 23		kg   pal. 805
<input checked="" type="checkbox"/> Glued laying		
<input checked="" type="checkbox"/> Suitable for underfloor heating <small>when gluing the entire area with solvent-free adhesives</small>		

