TYPES OF WOOD ALDER natural|steamed - ASH - BEECH natural|steamed - BIRCH BLACK WALNUT steamed - CHERRY natural|steamed - ELM steamed MAPLE - OAK - PEAR steamed - SMOKED OAK - SMOKED ZIRNOAK



Woodtype	OAK european
Description	3 layers of the same hardwood. The European Oak has a middle brown to intensive brown colour. The sorting Design is slightly to very knotty, with a lively structure.
Brinell hardness Gross density	4,2 kp 0,71 g cm³

## 1-Strip Country House Flooring OAK european Design "Villach" B190



## Surfaces

- Oil | wax oxidative dried
- Varnished 7-times
- ☑ Untreated sanded
- ☑ Brushed
- 🗹 Bevel
- $\checkmark$  Special colour



## Sorting guidelines

Healthy knots	allowed (partly filled)
Black knots	allowed (partly filled)
Healthy red heart	not allowed
Healthy black heart	not allowed
Cracks	allowed (partly filled)
Curled Spots   differences in structure	allowed
Natural colour differences	allowed
Natural fiber orientation	allowed
Wormholes and insect-ate-spots	not allowed are allowed in middle layer and back layer**
Sapwood	partly allowed
Red or brown spots	allowed
Stains from storage and light blueness	allowed
Knocked spots	not allowed
Mirror	alongside and crosswise allowed

Symbol picture - may vary in colour and structure

Technical data					
Thickness Width	15 mm 190 mm		Useful layer approx. 5 mm		
Length	Lengthsyster (6 layers   pkg		5 layers 1900 mm 1 layer 950* mm		
Connection Tongue and groove Due to the technical drying, there are no longer any pests, only the holes in the middle layer and back layer**					
m² pkg. 2,17			m² pal. 97,65		
kg pkg. 22		k	kg pal. 990		
✓ Floating laying					
✓ Glued laying					
Suitable for underfloor heating when gluing the entire area with solvent-free adhesives					

